

DECLARATION OF PERFORMANCE Nº 2013071210

1. Product-type:
HPL composite panel reference HYTEK (Thickness: 14 mm)
2. Name & contact address of the manufacturer:
Parklex International,s.l.
Polígono Alkaiga, C/Baldrun 1
31.780 Bera – Navarra (Spain)
3. Intended use of the construction product:
As internal finishes in floorings.
4. System of assessment and verification of the constancy of performance: 3
5. Notified body:
 - Tecnalia Research & Innovation NB 1292
 - Reaction to fire for initial type testing
 - System 3
6. Declared performance:

Essential characteristics	Performance	Harmonized technical specifications
Reaction to fire	B _{fl} -S ₁	EN 14.041:2004
Content of pentachlorophenol	< 5 ppm	
Release of formaldehyde	CLASS E1	
Water tightness	Water tight	
Slide resistance	DS	
Electric behaviour	Antistatic	
Thermal conductivity	0,17 w /m * k	
Reaction to fire durability	NPD	

- The performance of the product identified in point 1 is in conformity with the declared performance in point 6
- This declaration performance is issued under the sole responsibility of the manufacturer identified in point 2
- Signed for and on behalf of the manufacturer by: Iñigo Rodrigo (General Director)

Signature:

Place and date of issue:

 **Parklex®**
www.parklex.com

Bera, the 31st of May 2017